

DART SERVICE INSTRUCTION






TO AMEND INSTALLATION INSTRUCTIONS IIN-D120-638 Rev. A
 REF TCCA STC: SH99-221
 REF FAA STC: SR01177NY
 REF EASA STC: EASA.IM.R.S.01451

IT IS NOT NECESSARY TO REMOVE WEARPLATES / WEARPADS ON THE BOTTOM OF THE SKIDTUBES WHEN INSTALLING THE D120-638-011 BEARPAW INSTALLATION. THE BEARPAW MAY BE RELIEVED TO CLEAR WEARSHOE MOUNTING SCREWS PROVIDED THE RELIEF LEAVES 0.375" (9.53mm) THICKNESS.

CANADA
 DEPARTMENT OF TRANSPORT
 AIRCRAFT CERTIFICATION
 BRANCH
 DAO # 01-O-01

APPROVED
 BY: 
 D. SHEPHERD (DE # 02)

DATE: 09.11.05
 CERT. NO.: SH99-221
 ISSUE NO.: 1

A	NEW ISSUE	CP	09.11.05
REV.	DESCRIPTION	BY	DATE
DESIGN		DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN			
CHECKED		DRAWING NO. REV. A DSI 9491 SHEET 1 OF 1	
MFG. APPR.			
APPROVED		TITLE SCALE INSTALL MOD. NTS	
DE APPR.			
DATE 09.11.05		<small> COPYRIGHT © 2009 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD. </small>	